



# Declaration of Performance



Product:	4mm to 12mm toughened glass
Intended Use:	Thermally toughened soda lime silicate glass intended to be used in buildings and construction works
Manufacturer:	Cystal Units Limited, 100 West Hendon Broadway, London, NW9 7AA
Year marking was affixed:	07
AVCP System Number:	3
Applicable Standard:	BS EN 12150-2
Third Party Approval Licence No.	KM 530625
Notified Body / Number:	BSI Group / 2797
Person Empowered to Sign the DOP on behalf of the Manufacturer & Position Held:	Phil Hallworth - Technical & Sales Director

Essential Characteristics	Performance
---------------------------	-------------

### Safety in the case of fire

Resistance to fire (for glass for use in a glazed assembly intended specifically for fire resistance)	NPD
Reaction to fire	A1
External fire performance (for roof coverings only)	NPD

### Safety in use

Bullet resistance: Shatter properties and resistance to attack	NPD
Explosion resistance: Impact behaviour and resistance to attack	NPD
Burglar resistance: Shatter properties and resistance to attack	NPD
Pendulum body impact resistance: Shatter properties (safe breakability) and resistance to impact	1C1
Mechanical resistance: Resistance against sudden temperature changes and temperature differentials	200 K
Mechanical resistance: resistance against wind, snow, permanent and imposed and/or imposed loads of the glass unit and edge seal	4mm - 12mm

### Protection against noise

Direct airborne sound reduction	NPD
---------------------------------	-----

### Thermal properties

Normal Emissivity	NPD
U-value (W/m <sup>2</sup> K)	NPD

### Radiation Properties

Light Transmittance	NPD
Light Reflection	NPD
Solar Energy Characteristics	NPD
Direct solar transmittance	NPD
Direct solar reflectance	NPD
solar factor (g-value)	NPD

The performance of the product identified above is in conformity with the set of declared performance(s). This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above