



Declaration of Performance

Product:	4mm annealed clear - 12mm cavity - 4mm annealed clear	
Intended Use:	Insulting glass units intended to be used in buildings and construction works	
Manufacturer:	Cystal Units Limited, 100 West Hendon Broadway,	
	London, NW9 7AA	
Year marking was affixed:	13	
AVCP System Number:	3	
Applicable Standard:	BS EN 1279-5	
Third Party Approval Licence No.	KM 530625	
Notified Body / Number:	BSI Group / 2797	
Person Empowered to Sign the		
DOP on behalf of the	Phil Hallworth - Technical & Sales Director	
Manufacturer & Position Held:		

Essential Characteristics	Performance	
Safety in the case of fire		
Resistance to fire (for glass for use in a glazed assembly intended	NPD	
specifically for fire resistance)	NPD	
Reaction to fire	A1 / A1	
External fire performance (for roof coverings only)	NPD	
Safety in use		
Bullet resistance: Shatter properties and resistance to attack	NPD	
Explosion resistance: Impact behaviour and resistance to attack	NPD	
Burglar resistance: Shatter properties and resistance to attack	NPD	
Pendulum body impact resistance: Shatter properties (safe		
breakability) and resistance to impact	NPD	
Mechanical resistance: Resistance against sudden temperature		
changes and temperature differentials	40 K / 40 K	
Mechanical resistance: resistance against wind, snow, permanent		
and imposed and/or imposed loads of the glass unitand edge seal	4mm / 4mm	
Protection against noise		
Direct airborne sound reduction	30 (-1;-3) dB	
Thermal properties		
Normal Emissivity	0.89 / 0.89	
U-value (W/m²K)	2.8	
Radiation Properties		
Light Transmittance	NPD	
Light Reflection	NPD	
Solar Energy Characteristics	NPD	
Direct solar transmittance	NPD	
Direct solar reflectance	NPD	
solar factor (g-value)	NPD	