Declaration of Performance



Product:	4mm to 12mm heat soaked toughened glass	
Intended Use:	Heat soaked thermally toughened soda lime silicate	
	glass intended to be used in buildings and construction	
	works	
Manufacturer:	Cystal Units Limited, 100 West Hendon Broadway,	
	London, NW9 7AA	
Year marking was affixed:	16	
AVCP System Number:	3	
Applicable Standard:	BS EN 14179-2	
Third Party Approval Licence No.	KM 530625	
Notified Body / Number:	BSI Group / 2797	
Essential Ch	aracteristics	Performance
Safety in the case of fire		
Resistance to fire (for glass for use	in a glazed assembly intended	NPD
specifically for fire resistance)		NPD
Reaction to fire		A1
External fire performance (for roof coverings only)		NPD
Safety in use		
Bullet resistance: Shatter properties and resistance to attack		NPD
Explosion resistance: Impact behaviour and resistance to attack		NPD
Burglar resistance: Shatter properties and resistance to attack		NPD
Pendulum body impact resistance: Shatter properties (safe		
breakability) and resistance to impact		1C1
Mechanical resistance: Resistance against sudden temperature		
changes and temperature differentials		200 K
Mechanical resistance: resistance against wind, snow, permanent		
and imposed and/or imposed loads of the glass unitand edge seal		4mm - 12mm
Protection against noise		-
Direct airborne sound reduction		NPD
Thermal properties		
Normal Emissivity		NPD
U-value (W/m ² K)		NPD
Radiation Properties		
Light Transmittance		NPD
Light Reflection		NPD
Solar Energy Characteristics		NPD
Direct solar transmittance		NPD
Direct solar reflectance		NPD
Solar factor (g-value)		NPD

The performance of the product identified above is in conformity with the set of declared performance(s). This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above

Signed on behalf of the manufacturer by: 100 West Hendon Broadway, London, NW9 7AA 04/12/2024

Phil Hallworth - Technical & Sales Director